Remarks on the Reverse Auction

Michael Kearns
Computer and Information Science
University of Pennsylvania

Conference on the FCC Incentive Auction
Stanford Institute for Economic Policy Research
February 26, 2013

Comments based largely on "Design of the FCC Incentive Auctions", Yeon-Koo Che, Phil Haile, MK on behalf of AT&T (thanks also to Lili Dworkin)

Sources of Complexity in the Reverse

- Bidding and Strategic
 - simple bidding rules
 - strategic simplicity
 - relatively transparent outcomes
- Interaction and Coordination with Forward
 - clearing targets and closing conditions
 - sequential vs. interleaved
- Computational and Algorithmic
 - selection of winners subject to feasible repacking of losers
 - worst-case intractability of all forms of repacking
 - must exploit "special structure" of repacking constraint network, valuations
- No Avoiding Complexity!

Possible Reverse Mechanisms

- VCG
 - truthfulness dominant strategy
 - hard to understand
 - most computationally difficult (multiple ILPs vs. feasibility checks)
 - may be an important benchmark
- Other Sealed Bid (e.g. Pay-as-Bid)
 - strategically complex
 - hard to analyze
- Descending Clock (MALS)
 - truthfulness weakly dominant strategy
 - relatively easy to understand
 - computationally challenging

Proposal: Single-Pass Descending Clock

- Run a single reverse with decreasing clearing targets (max to min)
- When a clearing target is reached, record winners and prices
- Continue clocks until final clearing target
- Forward: run using highest clearing target and reverse prices
- If closing conditions met, terminate; else continue with lower target
- Advantages:
 - no change in reverse incentives or strategy
 - no need to reconvene multiple reverse auctions
 - reverse bids determined at one time, no valuation leakage over time
 - simplifies a two-sided closing trial
- Potential disadvantages:
 - broadcasters may reveal more information
- Single-pass with proxy bidding
 - proxy takes reservation value, bids accordingly
 - main advantage: offline computations!

Algorithmic Challenges in the Reverse

- Regardless of mechanism, encounter repacking under interference
- Interference constraints are physical and complex
- Geographically regional, but propagate nationally ("daisy chain")
- Both co-channel and adjacent-channel constraints
- Many variants of the problem:
 - given repacking network and bids, find VCG winners and payments (ILP optimizations)
 - given same, find expenditure-minimizing winner set subject to repacking (other sealed)
 - given a proposed winner set, determine if losers can be feasibly repacked (clock)
- In the worst case, all are intractable and inapproximable!
- Main hopes:
 - customized algorithms tuned to the "special structure" of repacking constraints and broadcaster valuation models (need both inputs!)
 - empirical understanding of likely performance based on large-scale simulations
 - offline computation and precomputation

The Two Inputs

- Repacking Interference Constraints:
 - based on physical proximity of transmission towers, height, power, terrain,...
 - agnostic to DMAs, EAs, etc.
 - complex, but in principle can know in great detail
- Broadcaster Valuations:
 - may vary widely across broadcasters
 - may depend on broadcaster types, location, repacking difficulty,...
 - complex, and in principle cannot know in detail... but could consider plausible models
- In any reverse mechanism, interference and valuations will interact
 - e.g. in descending clock with truthful bidding, valuations determine order of exit
 - order of exit and interference network position determine complexity of repacking
- What do/could we know/model about these two inputs?
 - special structure of interference network
 - models of relationship of network position, geography or type to valuations
 - both could lead to specialized algorithms, simulations, assessment of difficulty, etc.

Structure of the Interference Network: Some Preliminary Analysis

Data Methodology


- Broadcaster dataset derived from FCC's CDBS and TV Query DBs (1/13)
 - records linked using Facility ID and Radio Service codes for full power (DT) and Class A stations (DC, CA) in UHF band
 - where multiple Facility IDs existed, selected location with highest power transmitter
 - because antenna height above average terrain (HAAT) is not provided for Class A stations, used antenna centerline above ground level (RCAGL)


Interference Calculations

- for co-channel interference, compared transmitter spacing to ensure interference contour did not intersect protected contour
- for protected contour, used 41 dBu contour
- for interference contour, used 15 dB D/U ratio (26 dBu contour) per 73.616(e)(1)(i)
- contour distances estimated using FCC website calculator (computes F(50,90) only for UHF DTV)
- for adjacent channel interference, used 73.623 requirements
- transmitter spacing must be < 24 km or > 110 km


West Coast


Within 5 degrees of NYC







Connected Components









Philadelphia-New York-Hartford-Boston: adjacent channel constraints only



Degree Distributions and Clustering





Correlations with degree:

- power: 0.19

- height: 0.38

population: 0.29

Northeast: 0.39

Clustering:

- N=1732, 34,201 edges
- background density: 0.023
- clustering coefficient: 0.73
- Strong locality, but very dense
- Factor via cutsets?

Models of Valuations

- What are the right/reasonable correlates of valuation?
- How are they related to repacking difficulty?
- Network Position
 - degree, centrality, betweenness...
 - most directly related to repacking complexity
- Geography
 - DMAs, EAs, Northeast corridor
- Broadcaster Types
 - commercial, non-profit, educational...

Auction Simulations

- Small-scale (single DMAs, 2 adjacent DMAs)
- Full-auction simulations (dynamics, winners, prices, etc.)
 - descending clock (and "myopic" repacking variant)
 - VCG
 - sealed pay-as-bid at full-info Nash
 - varying clearing target, number of repacking channels, valuations
 - subtlety for clock: feasibility of repacking subject to clearing targets?
- Permits comparison of solutions, prices, etc.
- Sample timings, CPU minutes
 - VCG: ~151 (single call to Matlab ILP ~22)
 - descending clock: ~0.7 (~n^2 calls to Minisat solver)
 - "myopic" clock: ~0.01